



PGI/GB 2003 / 0 0 2 8 4 3



The Patent Office

Concept House Cardiff Road Newport

South Wales NP10 8QQ

# PRIORITY DOCUMENT SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 22 July 2003

BEST AVAILABLE COPY

An Evacutiva Agancu of the Donortment of Trade and Indicate



Request for grant of a patent (See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in

ally and the second

The Patent Office

**Cardiff Road** Newport South Wales NP10 8QQ

Your reference

this form)

MC 1598 GB

Patent application number (The Patent Office will fill in this part)

0215384.9

- 4 JUL 2002

Full name, address and postcode of the or of (1) Johnson Matthey Public Limited Company cach applicant (underline all surnanus)

2-4 Cockspur Street, Trafalgar Square, London SW1Y 5BQ

(2) Aubin Limited Unit 1 Castle Street, Castlepark Industrial Estate, Ellon AB41 9RF, Scotland

If the applicant is a corporate body, give the

Patents ADP number (15 you know tt)

country/state of its incorporation

(1) GB

(2) Scotland

8755788007

53626 8007

4. Title of the invention

IMPROVEMENTS IN METAL SALTS

Name of your agent (if you have one)

IAN CARMICHAEL WISHART

"Address for scivice" in the United Kingdom JOHNSON MATTHEY TECHNOLOGY CENTRE to which all correspondence should be sent BLOUNTS COURT (imminding the postcode)

SONNING COMMON READING RG4 9NH

Patents ADP number (if you know it)

2256331001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these carlier applications and (4 you know is) the or each application number

Country

Priority application number (if you know it)

· Date of filing (day / momb / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing (day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer Yes' if:

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

 any named applicant is a corporate body. See note (d))

Yes

10040828112-10112-1-24

### ents Form 1/77

 Enter the number of sheets for any of the following items you are filing with this form.
 Do not count copies of the same document

Continuation sheets of this form 0
Description 5

Claim(s) 1

Abstract 1

Drawing(5)

If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Parens Form 7/77)

Request for preliminary examination and search (Patents Form 2/77)

ONE

Request for substantive examination
(Patents Form 10/77)

Any other documents (blease specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

sevit

Date 4 July 2002

I C WISHART

 Name and daytime telephone number of person to contact in the United Kingdom

MRS F E STRANGE 0118 924 2125

#### Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be probibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to probibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction probibiting publication or communication has been given, or any such direction has been revoked.

#### Notes

- a) If you need belp to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.





### IMPROVEMENTS IN METAL SALTS

5

10

The present invention concerns improvements in metal salts, more especially concerns the removal of certain ions from aqueous solutions.

It is commonplace in drilling for oil and gas, to use fluids such as brines as well servicing fluids. In general, such fluids have desirably a high density. In particular, highly concentrated alkali metal salts of carboxylic acids have been developed for use in oil and gas well drilling and completion operations. Such a fluid may be based upon cesium salts such as cesium formate, which can provide brines of specific gravity values of 1.8 to more than 2.1, depending upon solution concentrations.

15

20

25

30

During use of such brines, they may be contaminated with sodium chloride from sea water or from water or salt entrained within the rock and mud during application in the well bore. Chloride ions can cause severe corrosion of steel pipework and additionally may be incompatible with the rock matrix, causing damage to the near well bore area. Such problems may result in users of such brines refusing to re-use chloride-contaminated brines. A charge of cesium formate solution for use as an oil field brine may cost in the order of \$10M, so there is considerable need to improve the prospects for recycling such a brine.

Further, if a diluted brine is returned to high density by evaporation of water, any chloride concentration will increase by this process, thereby rendering the brine less suitable to use.

Accordingly, this invention can be applied to removal of chloride from brine both caused by contamination in use or caused by a concentration process such as evaporation, and throughout this description and claims the term "recovered brine" is to be understood as including brines which have been concentrated.

The present invention provides a method of treating an alkali metal carboxylate salt brine contaminated with chloride ion, comprising mixing such contaminated brine with a

solution of a silver salt, especially silver nitrate, causing silver chloride to be formed and separating the silver chloride from the residual brine.

The invention may also be expressed as a method of use of an alkali metal carboxylate salt brine, comprising the recovery of used brine contaminated with chlorida ion, treating the recovered brine with a solution of a silver salt, especially silver nitrate, causing silver chloride to be formed and separating the silver chloride from the brine, and re-using the brine. Desirably, the brine comprises cesium as the alkali metal, and formate, acetate or other species, as the salt anion. The brine may comprise mixtures of alkali metal carboxylates. Further, the brine may comprise one or more polymers or other components which are adjuvants and provide desirable properties to the brine or avoid disadvantages.

The preferred silver salt is silver nitrate, and for ease of description, all references hereinafter will be to silver nitrate.

15

20

25

5

10

Since the specific gravity of the brine is extremely important, it is desirable to minimise any loss of specific gravity by undue dilution during the treatment. Accordingly, it is desirable to use silver nitrate solutions containing at least 200g/l of AgNO<sub>3</sub>, more preferably at least 300g/l AgNO<sub>3</sub> and most preferably at least about 950g/l. At room temperature, saturation concentrations are about 1400g/l AgNO<sub>3</sub>. The silver nitrate solution may contain other components which do not significantly adversely interfere with the method of the invention, or the performance of the brine. The silver nitrate solution is conveniently a product stream from a process involving the manufacture of high purity silver nitrate. This can provide economics arising from heat and water savings and other processing costs.

The treatment of the invention is conveniently carried out at room temperature, but may be carried out at ambient temperature. It will be borne in mind that solubility decreases with decreasing temperature, and crystallisation may occur. Allowing the brine to cool to ambient temperature, or preferably cooling to about 0°C, facilitates the removal of sufficient

30

MC1598

5

10

15

3

cesium nitrate formed as a by-product to create a stable solution that can be supplied and used in winter conditions.

Conveniently, silver chloride may be removed from the brine by filtration: This is particularly applicable because of the relatively high value of the silver chloride. Other methods for separation may be used, however, such as hydrocyclones or centrifuges, and where applicable or desirable, polymeric materials may be added to enhance separation.

The treatment may be carried out in a two-step process, or, in a preferred embodiment, in a single step process. Desirably, at least a stoichiometric quantity of silver nitrate is used, relative to chloride ion, in the treatment. More desirably, the quantity of silver nitrate is from approximately 105% to approximately 115% stoichiometric, especially from 108 to 112% stoichiometric, for brines containing 13.5g/l chloride. If the brine has other chloride contents, the stoichiometric uplift may differ and can be established by trial and error.

The recovered silver chloride may carry entrained by-products such as silver formate and cesium nitrate. Under preferred conditions, these are minimised and removed to permit the production of a re-usable brine. By washing and crystallisation, silver chloride crystals may be obtained and the silver value recovered in conventional ways by conversion to other compounds or silver metal, using methods available to the person of ordinary skill in the art. In general, therefore, it is preferred to separate the silver chloride by filtration, but conventional washing of the solids is not desirable if it causes undue dilution of the filtrate. Entrained cesium formate in the filtered precipitate may be washed out subsequently, using water, and cesium nitrate may also be recovered if desired.

25

20

The skilled person may use the information herein to optimise the process, using conventional techniques.

The invention may be further understood with reference to the following Examples.

30

20

30

4

### EXAMPLE 1 Stoichiometric Additions of AgNO<sub>3</sub>

200 ml samples of a used cesium formate brine, containing 1587g/l cesium formate, 13.53g/l chloride, 0.720wt% sodium and 2.63 wt% potassium were used for all tests described. Desirably, the chloride level will be reduced below 1g/l, more preferably 0.3 - 0.7g/l.

In the first Example, stoichiometric amounts of AgNO<sub>3</sub> solution are added with stirring, to the brine, at room temperature and at differing concentrations:

AgNO <sub>3</sub> concn. (g/l)	150	200	600	918	1366
Volume added (ml)	87.6	65.7	.21.6	14.5	9.5
Cl concn. (g/l)	0.50	0.64	0.72-0.99	1.0	1.78
( all concentrations in a	y/l normalise	d to 200 m	l)		
Specific gravity	1.848	1.913	2.084	2.117	2.129

In order to produce a product brine having CI concentration of approximately 0.5g/l, combined with a specific gravity of not less than 2.0, a second stage treatment with AgNO<sub>3</sub> was undertaken, with the following results:

	First stage product Cl (g/l normalised)	0.99	1.00	1.78	
	AgNO <sub>3</sub> stoichiometry (%)	50	50	80	
25	AgNO <sub>3</sub> concn. (g/l normalised)		200	90	
	200				
	Final Cl concn. (g/l normalised)	0.54	0.51	0.44	
	Overall AgNO <sub>3</sub> stoichiometry (%)	103.2	103.4	110.0	
	Specific gravity	2.055	2.077	2.057	

After first and second stages, the deposits formed in the brine were filtered off.



5

## EXAMPLE 2 Single Stage Chloride Removal

The identical cesium formate brine as in Example 1 was used in further tests, using differing stoichiometries:

	Test No.	1	2	3
	AgNO₃ stoichlometry (%)	107	110	116
10	Vol. AgNO <sub>3</sub> soln. added (ml)	10.2	10.4	11
	CI concn. (g/l normalised)	0.58	0.35	<0.01
	Specific gravity	2.111	2.122	2.095

Tests 1 and 2 proceeded satisfactorily at room temperature. It was assessed in Test 3 that excess silver was being dissolved and a post-treatment of heating the product brine to 95°C was incorporated, to remove the silver in solution.

A further post treatment of cooling to approximately 0°C overnight followed by filtration, was found to remove a large proportion of by-product cesium nitrate, leaving a stable clear solution at room temperature.

### **CLAIMS**

10

- 1. A method of treating an alkali metal carboxylate salt brine contaminated with chloride ion, comprising admixing such contaminated brine with a solution of a silver salt, especially silver nitrate, causing silver chloride to be formed in a reaction mixture and separating the silver chloride from the residual brine.
- 2. A method according to claim 1, wherein the brine comprises cesium as the alkali metal and formate, acetate or other species as the salt anion.
- 3. A method according to claim 1 or claim 2, comprising the use of a silver nitrate solution containing at least 950g/l AgNO<sub>3</sub>.
- 4. A method according to claim 1,2 or 3, wherein by-product cesium nitrate is removed after cooling the reaction mixture, preferably to about 0°C.
  - 5. A method according to any one of the preceding claims, wherein silver nitrate used in a quantity of from 105 to 115% of stoichiometric.
- 20 6. A method according to any one of the preceding claims, carried out such that the residual brine has a specific gravity of not less than 2.0.
- 7. A method of use of an alkali metal carboxylate salt brine, comprising the recovery of used brine contaminated with chloride ion, treating the recovered brine with a solution of a silver salt, especially silver nitrate, causing silver chloride to be formed, separating the silver chloride from the brine, and re-using the brine.

MC1598GB/4July2002

MC1598

5

7

#### IMPROVEMENTS IN METAL SALTS

**Abstract of the Disclosure** 

Alkali metal carboxylate salt brines, such as cesium formate brine, are used in oil and gas drilling procedures. Contamination with chloride lons can be controlled by treatment with a silver salt solution, and removing silver chloride formed. High density brines can be obtained, suitable for re-use.

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

### **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

### IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.